





2/2 Way Piston Actuated Valve G 1/2" to 2", Regular Version - Stainless Steel

Specifications	
Type: PG NC flow over seat 1 → 2	
Type: RPG NO flow under seat 2 → 1	
Type: BPG NC bi-directional flow over/under seat 1 → 2 / 2 → 1	
Type: DPG DA flow over/under seat 1 ↔ 2	
Media	Water, oil, air, aggressive media, steam ¹
Media Temperature	-10 to +180 °C
Ambient Temperature	-10 to +60 °C
Pilot Media ²	Instrument air, inert gases
Body Material	Cast AISI 316L (CF3M), see page 7
Bonnet Material	Cast AISI 316L (CF3M), see page 7
Actuator Body Material	Polyamide PA6 (reinforced fiberglass 30%)
Seal Material	PTFE
Position Indicator	As standard

Features and Benefits


- Waterhammer-free design for BPG - DPG (with flow direction 2 → 1)
- Actuator housing rotation 360°
- Design suitable for vacuum applications up to 10⁻² mbar



Options Available	
Stroke regulator assembled ex-factory, see page 33 (e.g. code RPG210STJR0)	
Travel switch assembled ex-factory, see page 33 (e.g. code PG208STZJ0)	
NPT connection (e.g. code BPN207LTY00)	
High temperature version, see pages 24/25 (e.g. code PG205STW0H)	

Accessories
Position module, travel switch kit, pilot solenoid valves see pages 34/35/36

Dimensions & Weights		DN15	DN20	DN25	DN32	DN40	DN50	DN25	DN32	DN40	DN50
Actuator	[mm]	Ø 63						Ø 90			
A	[mm]	65	75	90	110	120	150	90	110	120	150
B	[mm]	192	198	212	225	230	248	223	234	239	257
C	[mm]	184	192	205	217	225	241	216	227	235	250
D	[mm]	171	176	185	193	198	207	196	202	207	216
E	[mm]	85	85	85	85	85	85	112	112	112	112
Weight	[kg]	1.2	1.3	1.5	1.9	2.1	2.9	2.0	2.4	2.6	3.3



The products listed below comply with the requirements of the European Pressure Equipment Directive 2014/68/UE and carry the CE mark when required. The products fall within the following Pressure Equipment Directive categories:

Valve Type	Bodies	Group 1 gases	Group 1 liquids and Group 2 other fluids
PG - RPG - BPG - DPG	DN15 to DN25 (PN40)	art. 4.3	art. 4.3
	DN32 to DN40 (PN25)	Category I	art. 4.3
	DN50 (PN16)	Category I	art. 4.3

⚠ WARNING!

According to the European Pressure Equipment Directive 2014/68/UE, liquids whose saturated vapour pressure at the maximum allowable temperature is more than 0,5 barg shall be considered as gases.

2/2 Way Piston Actuated Valve G 1/2" to 2", Regular Version – Stainless Steel

Valve	Body Connection	DN	Flow Rate Kvs	Working Pressure ¹		Flow Direction	Pilot Pressure ³		Actuator Ø	Function
Code	[ISO 228G]	[mm]	[l/min]	[barg]	[barg]	—	[barg]	[barg]	[mm]	—
PG205STW00	1/2"	15	87	0	20	1 → 2	3.7	10	63	NC
PG206STX00	3/4"	20	164	0	20	1 → 2	4.4	10		
PG207STY00	1"	25	260	0	20	1 → 2	5	10		
PG208STZ00	1 1/4"	32	410	0	16	1 → 2	5.9	10		
PG209STK00	1 1/2"	40	700	0	16	1 → 2	9	10		
PG210STJ00	2"	50	950	0	11	1 → 2	8	10		
PG207LTY00	1"	25	260	0	20	1 → 2	2	8	90	
PG208LTZ00	1 1/4"	32	410	0	16	1 → 2	3.5	8		
PG209LTK00	1 1/2"	40	700	0	16	1 → 2	4	8		
PG210LTJ00	2"	50	950	0	15	1 → 2	6.5	8		
RPG205STW00	1/2"	15	87	0	16	2 → 1	2.5	8	63	NO
RPG206STX00	3/4"	20	164	0	16	2 → 1	4.3	8		
RPG207STY00	1"	25	260	0	16	2 → 1	5.5	8		
RPG208STZ00	1 1/4"	32	410	0	16	2 → 1	6.5	8		
RPG209STK00	1 1/2"	40	700	0	12	2 → 1	8	8		
RPG210STJ00	2"	50	950	0	8	2 → 1	8	8		
RPG207LTY00	1"	25	260	0	16	2 → 1	2	5	90	
RPG208LTZ00	1 1/4"	32	410	0	16	2 → 1	4	5		
RPG209LTK00	1 1/2"	40	700	0	16	2 → 1	5	5		
RPG210LTJ00	2"	50	950	0	10	2 → 1	5	5		
BPG205STW00	1/2"	15	87	0	16	1 → 2 / 2 → 1	5.5 / 3.8	10	63	NC bidirectional
BPG206STX00	3/4"	20	164	0	16	1 → 2 / 2 → 1	6 / 3.8	10		
BPG207STY00	1"	25	260	0	16 / 11	1 → 2 / 2 → 1	6.5 / 3.8	10		
BPG208STZ00	1 1/4"	32	410	0	16 / 6	1 → 2 / 2 → 1	6.8 / 3.8	10		
BPG209STK00	1 1/2"	40	700	0	12 / 4	1 → 2 / 2 → 1	9 / 3.8	10		
BPG210STJ00	2"	50	950	0	8 / 2.5	1 → 2 / 2 → 1	9 / 3.8	10		
BPG207LTY00	1"	25	260	0	16 / 14	1 → 2 / 2 → 1	4 / 3.3	8	90	
BPG208LTZ00	1 1/4"	32	410	0	16 / 12	1 → 2 / 2 → 1	5 / 3.3	8		
BPG209LTK00	1 1/2"	40	700	0	16 / 8	1 → 2 / 2 → 1	6 / 3.3	8		
BPG210LTJ00	2"	50	950	0	14 / 6	1 → 2 / 2 → 1	8 / 3.3	8		
DPG205STW00	1/2"	15	87	0	16	1 ↔ 2	1.8	2	63	DA
DPG206STX00	3/4"	20	164	0	16	1 ↔ 2	2	3.8		
DPG207STY00	1"	25	260	0	16	1 ↔ 2	3	5		
DPG208STZ00	1 1/4"	32	410	0	16	1 ↔ 2	4.5	6		
DPG209STK00	1 1/2"	40	700	0	16	1 ↔ 2	6.5	7		
DPG210STJ00	2"	50	950	0	10	1 ↔ 2	8	8		

Notes

1. Steam max. working pressure 10 bar (9 barg)
2. Please contact M&M sales Department for other pilot media
3. Minimum pilot pressure at the max. working pressure: for lower working pressures please refer to the comparative charts