DEMA 294 DC
FOAM GENERATOR SYSTEM



A new designed foam generator for foam cleaning applications in the car wash industry, food industry, restaurants and agricultural applications

Features:

- **Compact design with polished stainless steel cover**
- **Uses the new corrosion resistant 294D foam generator of PVC**
- **Supplied with air pressure regulator and gauge for exact on-site settings of foam quality**
- **Capacity 170 liters of foam per minute at 4,2 bars**
- **Different gun and hose kits available as option with quick connector fittings.**
- **Foam wands in Stainless steel or PVC available as option.**
- **Supplied with suction, tubing, weight and metering tips for simplified setting of dilution rates.**

Technical information

Measurements W x H x D	**: 220 x 85 x 170mm**
Ship weight	**: 1,7 Kg´s**
Capacity	**: 170 liters of foam per minute**
Water pressure	**: 3 bars min. recommended**
Air pressure	**: 6 bars, 100 ltrs per minute recommended**
Seal material, standard	**: EPDM**
Optional	**: Viton**
Mounting position	**: To a flat surface**
Maximum suction height	**: 1700 mm recommended**
Connections	
Water inlet	**: ¾" female GHT**
Foam outlet	**: ¾" male GHT or quick connector on request**
Air inlet	**: ¼" female NPT**
Materials	
Body	**: PVC**
Cover	**: Polished Stainless Steel**
Water/air pipe work	**: Brass**
Backflow preventer	**: Class BA as option**